

Glasstex[®]Grid R60 - Paving Grid

Intended use: Glasstex[®]Grid R60 is an asphalt interlayer (Paving Grid) used in road constructions to mitigate reflective cracking from bound substrates into newly paved asphalt layers.

Product description: Glasstex[®]Grid R60 consists of a glass filament grid structure stitched onto a lightweight veil. The product is penetrated with a polymer modified coating and provides a reinforcing function by the high tensile glass filaments. The veil acts as an installation aid only and supports fixing the product during installation due to its continuous structure.

Provided function: Reinforcement (R)

Characteristic	Unit	Value
Roll width (1)	m	1/2/3/4
Roll length	m	100
Product weight according EN ISO 9864	g/m ²	285
Mesh size	mm	25 × 25
Index strength according EN ISO 10319	kN/m	60
Typical strain at failure according EN ISO 10319	%	≤3.0
Elastic modulus of glass filaments (2)	GPa	73
Softening Point of the Grid	°C	>800

(1) On request

(2) Typical value

(3) Glasstex[®]Grid R60 is manufactured in accordance with a Quality Management System which complies with the requirements of EN ISO 9001.

(4) All quoted dimensions and values are typical unless stated otherwise.

The information in this document supersedes any and all prior Technical Notes for the product(s) designated above, is of an illustrative nature and supplied by Tensar International Limited free of charge for general information purposes only. Tensar reserves the right to amend product descriptions, properties and specifications at any time and without prior notice. This document does not form part of any contract or intended contract. Tensar International Limited excludes to the fullest extent lawfully permitted any and all liability whatsoever for any loss or damage howsoever arising out of the use of and reliance upon this information. It is your sole responsibility and you must assume all risk and liability for the final determination as to the suitability of any Tensar International Limited product and/or design for the use and in the manner contemplated by you in connection with a particular project.

Tensar and TriAx are registered trademarks

Copyright © Tensar International Limited 2019

Tensar International Limited

Tel: **+44 (0) 1254 262431**
 Fax: **+44 (0) 1254 266867**
 E-mail: **sales@tensar.co.uk**
www.tensar-international.com

UK Head Office

**Units 2 - 4 Cunningham Court
 Shadsworth Business Park
 Blackburn
 BB1 2QX
 United Kingdom**

